

Styromagnesit Steirische Magnesitindustrie GmbH

STYROMAG® OT/S

Characteristics:

STYROMAG® OT/S is very active magnesia powder, produced by the use of crystalline and cryptocrystalline raw magnesites, which is mainly used for the production of grinding and mill stones.

	method		typical	
Chemical data:	MgO	AA8.2.1.1.*	[%]	85,0
	CaO	AA8.2.1.3. – RF.	A* [%]	4,0
	CaO _{active}	AA8.2.1.1.*	[%]	0,6
	Fe ₂ O ₃	AA8.2.1.3. – RF.	A* [%]	2,5
	SiO ₂	AA8.2.1.3. – RFA* [%]		4,0
	L.O.I.	1050°C/1h	[%]	5,0
Physical data:	bulk density	EN 14016-2	[kg/dm³]	0,6 – 0,7
	residue on sieve	EN 14016-2		
	200 μm		[%]	1,0
	90 μm		[%]	13,0
	Setting time***	AA8.2.1.5.*		range
	start		[min]	30 - 170
	end		[min]	50 - 200

^{***}setting times (MgCl2-solution, 20°Bé) are adjusted according to the customer's requirements

Storage stability:

6 months from production date when stored in a dry place in unopened original packaging

The data given above is typical values targeted by our production and are checked by our quality control with the help of the mentioned methods. It is still the user's duty to control the product upon delivery. We reserve the right to modify the manufacturing process of this product. As our product is a processed natural mineral, variations in the concentration of accompanying minerals are possible. This edition cancels and replaces all previous editions of this document.

OTS DS Oberdorf, 10.02.2016



UID-Nr.:

Firmensitz: St. Katharein / Laming - Oberdorf 41 Firmenbuchgericht: Handelsgericht Leoben Firmenbuchnummer: FN141746a

DVR Nr.: 0470732 EVA Nr.: 112648







^{*.....} internal test method