

Styro magnesit Steirische Magnesitindustrie GmbH

STYROMAG® BR 80

Characteristics: STYROMAG® BR 80 is very active magnesia powder, which is

mainly used for the production of brake linings.

		method		typical
Chemical data:	MgO	AA8.2.1.1.*	[%]	81,0
	CaO	$AA8.2.1.3 RFA^*$	[%]	5,0
	Fe ₂ O ₃	$AA8.2.1.3 RFA^*$	[%]	2,0
	SiO_2	$AA8.2.1.3 RFA^*$	[%]	5,0
	L.O.I.	1050°C/1h	[%]	6,0

Physical data:	bulk density	EN 14016-2	[kg/dm ³]	0,6-0,7
	residue on sieve	EN 14016-2		
	200 μn	1	[%]	0,3
	90 μn	1	[%]	8,0

Storage stability:

12 months from production date when stored in a dry place in unopened original packaging

The data given above is typical values targeted by our production and are checked by our quality control with the help of the mentioned methods. It is still the user's duty to control the product upon delivery. We reserve the right to modify the manufacturing process of this product. As our product is a processed natural mineral, variations in the concentration of accompanying minerals are possible. This edition cancels and replaces all previous editions of this document.

BR80 DS Oberdorf, 02.02.2016



Firmensitz: St. Katharein / Laming - Oberdorf '41 Firmenbuchgericht: Handelsgericht Leoben Firmenbuchnummer: FN141746a

DVR Nr.: 0470732 EVA Nr.: 112648

BKS Bank AG, 8010 Graz BIC BEKKAT2K





^{*.....} internal test method