

Styromagnesit Steirische Magnesitindustrie GmbH

STYROMAG® G 80

Characteristics: STYROMAG® G 80 is very active magnesia powder, which is mainly

used in the building industry and in the chemical industry.

		method		typical
Chemical data:	MgO	AA8.2.1.1.*	[%]	80,0
	CaO	$AA8.2.1.3 RFA^*$	[%]	4,5
	Fe_2O_3	$AA8.2.1.3 RFA^*$	[%]	4,0
	SiO_2	$AA8.2.1.3 RFA^*$	[%]	5,0
	L.O.I.	1050°C/1h	[%]	7,0

Physical data:	bulk density	EN 14016-2	[kg/dm ³]	0,7-1,0
	residue on sieve	EN 14016-2		
	200 μn	1	[%]	3,0
	90 μn	n	[%]	40,0
	Setting time***	AA8.2.1.5.*		range
	star	rt	[min]	20 - 300
	en	d	[min]	40 - 350

^{***}setting times (MgCl2-solution, 20°Bé) are adjusted according to the customer's requirements

Storage stability:

6 months from production date when stored in a dry place in unopened original packaging

The data given above is typical values targeted by our production and are checked by our quality control with the help of the mentioned methods. It is still the user's duty to control the product upon delivery. We reserve the right to modify the manufacturing process of this product. As our product is a processed natural mineral, variations in the concentration of accompanying minerals are possible. This edition cancels and replaces all previous editions of this document.

G80 DS Oberdorf, 02.02.2016



Firmensitz: St. Katharein / Laming - Oberdorf 41 Firmenbuchgericht: Handelsgericht Leoben Firmenbuchnummer: FN141746a UID-Nr.:

ATU39956909

DVR Nr.: 0470732 EVA Nr.: 112648





^{*.....} internal test method