

Styromagnesit Steirische Magnesitindustrie GmbH

## STYROMAG<sup>®</sup> Gulsenit 0/60

<u>Characteristics:</u>	STYROMAG Gulser specific surface.	nit 0/60 consists	s of natural	silicates with a high
		method		typical
<u>Chemical data:</u>	SiO <sub>2</sub>	AA8.2.1.11.*	[%]	78,0
	MgO	AA8.2.1.11.*	[%]	5,0
	CaO	AA8.2.1.11.*	[%]	0,9
	$R_2O_3$	AA8.2.1.11.*	[%]	7,0
	L.O.I.	1050°C/1h	[%]	8,0
<u>Physical data:</u>	grain size			
	> 60 µm	Sedigraph	[%]	27
				range
	bulk density	EN 14016-2[kg/dm <sup>3</sup> ] AA8.2.1.8.* – BET [m <sup>2</sup> /g]		0,65 - 0,75
	specific surface			100 – 120

\*..... internal test method

The data given above is typical values targeted by our production and are checked by our quality control with the help of the mentioned methods. It is still the user's duty to control the product upon delivery. We reserve the right to modify the manufacturing process of this product. As our product is a processed natural mineral, variations in the concentration of accompanying minerals are possible. This edition cancels and replaces all previous editions of this document.

